

FIG. 1




FIG. 2




FIG. 3

Contextual Information for Data Signature Evaluation

Data Signature	Context	Severity/Alert Condition (0-5)
"/cgi-bin/phf"	HTTP URL	4
"/cgi-bin/phf"	Email header	0
"/cgi-bin/phf"	HTML HREF	3
".exe"	TFTP filename	2

FIG. 4

Exemplary Fingerprint Requests and Target Responses

FTP (file transfer):

220 rh5.robertgraham.com FTP server (version wu-2.4.2-academ [BETA-15] (1) Sat Nov 1 03:08:32 EST 1997) ready.

Telnet

Red Hat Linux release 5.0 (Hurricane)
kernel 2.0.31 on an i486
login:

SMTP (mail)

220 rh5.robertgraham.com ESMTP Sendmail 8.8.7/8.8.7; Mon, 29 Nov 1999 23:28:31-0800

Finger (user information)

Login Name	Tty	Idle	Login Time	office	office
Phone					
rob	Robert David Graham	p0	Nov 29 22:51		(gandalf)
root	root		p1	Nov 29 23:34	
(10.17.128.201:0.0)					

HTTP

HTTP/1.0 200 OK
Date: Tue, 30 Nov 1997 07:34:59 GMT
Server: Apache/1.2.4
Last-Modified: Thu, 06 Nov 1997 18:20:06 GMT
Accept-Ranges: bytes
Content-Length: 1928
Content-Type: text/html

HTTP

Date: Fri, 01 Jun 2001 20:38:03 GMT
Server: Apache/1.3.14 (Unix) (Red-Hat/Linux) mod_ssl/2.7.1 OpenSSL/0.9.5a DAV/1.0.2
PHP/4.0.4p11 mod_perl/1.2.4
Last-Modified: Wed, 18 Oct 2000 22:31:33 GMT
ETag: "9327c-b4a-39ee24c5"
Accept-Ranges: bytes
Content-Length: 2890
Connection: close
Content-Type: text/html

POP3

+OK POP3 rh5.robertgraham.com v4.39 server ready

IMAP

* OK rh5.robertgraham.com IMAP4rev1 v10.190 server ready

SMB

SMB: ----- Setup Account AndX Header -----
SMB:
SMB: Word count = 3
SMB: Parameter words = 750080000000
SMB: Byte Count = 87
SMB: Byte parameters = 00570069006E006400....
SMB: AndX command = 75 (Tree Connect AndX)
SMB: AndX reserved(MBZ) = 00
SMB: AndX offset = 0080
SMB: Request Mode = 0000
SMB:0 = Not logged in as 'Guest'
SMB: Byte Count = 87
SMB: Server's Native OS = Windows NT 4.0
SMB: Server's Native LAN Man = NT LAN Manager 4.0
SMB: Server's Primary Domain = AMPHLETT

FIG. 5

Target Vulnerabilities

Target Fingerprint	Data Signature (may be context-based)	Severity/Alert Condition (0-5)
OS: Apache Ver >= 1.2 Processor: any BIOS: any	"/cgi-bin/phf" in HTTP Header	0
OS: Apache Ver < 1.2 Processor: any BIOS: any	"/cgi-bin/phf" in HTTP Header	4
OS: IIS Processor: any BIOS: any	"/cgi-bin/phf" in HTTP Header	0
OS: Netscape Enterprise Server Processor: any BIOS: any	"/cgi-bin/phf" in HTTP Header	0
OS: any Processor: Intel BIOS: any	09090909	3
OS: any Processor: Non-Intel BIOS: any	09090909	0

FIG. 6




FIG. 7

220 mandrake.intra.networkkice.com FTP server (Version wu-
2.5.0(1) Sat May 22 11:15:07 GMT 1999) ready.

-> USER rob

331 Password required for rob.

-> PASS Cerveza2

230 User rob logged in.

-> SYS RETR /etc/passwd

500 'SYS RETR /etc/passwd': command not understood.

-> PORT 10,10,0,135,4,1

200 PORT command successful.

-> RETR /etc/passwd

150 Opening ASCII mode data connection for /etc/passwd
(2661 bytes).

226 Transfer complete.

-> RNFR /etc/passwd

350 File exists, ready for destination name

-> RETR /tmp/etc/passwd

550 /tmp/etc/passwd: No such file or directory.

-> QUIT

221-You have transferred 2719 bytes in 1 files.

221-Total traffic for this session was 3397 bytes in 1
transfers.

221-Thank you for using the FTP service on
mandrake.intra.networkkice.com.

221 Goodbye.

FIG. 8

Excerpt from RFC 959

For each command or command sequence there are three possible outcomes: success (S), failure (F), and error (E). In the state diagrams below we use the symbol B for "begin", and the symbol W for "wait for reply".




FIG. 9

Snort 1.7 Signature

```
alert TCP $EXTERNAL any -> $INTERNAL 21 (  
  msg: "IDS213/ftp_ftp-passwd-retrieval-retr";  
  content: "RETR"; nocase;  
  content: "passwd";)
```

Sample signature using one embodiment of the present system

```
alert TCP $EXTERNAL any -> $INTERNAL $FTP (  
  msg: "IDS213/ftp_ftp-passwd-retrieval-retr";  
  FTP.filename: "*/passwd";  
  FTP.banner: "*Version wu-2*";  
  FTP.response: "2??";  
  FTP.response: "3??";  
)
```

FIG. 10

```
alert TCP $EXTERNAL any -> $INTERNAL $HTTP (  
  msg: "system32/cmd.exe";  
  HTTP.url: "*/system32/cmd.exe";  
  HTTP.server: "IIS/*";  
  +HTTP.response: "5??";  
  -HTTP.response: "4??";  
  -HTTP.response: "2??";  
)
```

```
alert TCP $EXTERNAL any -> $INTERNAL $HTTP (  
  msg: "IIS malformed HTW";  
  HTTP.url.extension: "/*.htw";  
  HTTP.server: "IIS/*";  
  -HTTP.response: "5??";  
  -HTTP.response: "4??";  
  +HTTP.response: "2??";  
)
```

FIG. 11

RedHat 6.2

program	vers	proto	port	
100000	2	tcp	111	portmapper
100000	2	udp	111	portmapper
100021	1	udp	1024	nlockmgr
100021	3	udp	1024	nlockmgr
100021	1	tcp	1024	nlockmgr
100021	3	tcp	1024	nlockmgr
100024	1	udp	980	status
100024	1	tcp	982	status

RedHat 7.0

program	vers	proto	port	
100000	2	tcp	111	portmapper
100000	2	udp	111	portmapper
100021	1	udp	1024	nlockmgr
100021	3	udp	1024	nlockmgr
100024	1	udp	1025	status
100024	1	tcp	1024	status

Solaris 8

program	vers	proto	port	
100000	4	tcp	111	portmapper
100000	3	tcp	111	portmapper
100000	2	tcp	111	portmapper
100000	4	udp	111	portmapper
100000	3	udp	111	portmapper
100000	2	udp	111	portmapper
100232	10	udp	32772	sadmind
100011	1	udp	32773	rquotad
100002	2	udp	32774	rusersd
100002	3	udp	32774	rusersd
100002	2	tcp	32771	rusersd
100002	3	tcp	32771	rusersd
100012	1	udp	32775	sprayd
100008	1	udp	32776	walld
100001	2	udp	32777	rstatd
100001	3	udp	32777	rstatd
100001	4	udp	32777	rstatd
100024	1	udp	32778	status
100021	1	udp	4045	nlockmgr
100021	2	udp	4045	nlockmgr
100021	3	udp	4045	nlockmgr
100021	4	udp	4045	nlockmgr
100024	1	tcp	32772	status
100133	1	udp	32778	
100133	1	tcp	32772	
100083	1	tcp	32773	
100221	1	tcp	32774	
100235	1	tcp	32775	
100021	1	tcp	4045	nlockmgr
100021	2	tcp	4045	nlockmgr
100021	3	tcp	4045	nlockmgr
100021	4	tcp	4045	nlockmgr
100068	2	udp	32779	
100068	3	udp	32779	
100068	4	udp	32779	
100068	5	udp	32779	
300326	4	tcp	32776	
300598	1	udp	32786	
300598	1	tcp	32778	
805306368	1	udp	32786	
805306368	1	tcp	32778	
100249	1	udp	32787	
100249	1	tcp	32779	
1289637086	5	tcp	32803	
1289637086	1	tcp	32803	

FIG. 12